


MASK





wall recessed

wall recessed

Device to be wall recessed with minimum size which particular design from sleek lines, is drawn to maximize the effect of light and at the same time characterize its form. When switched off, Mask provides with a particular graphic sign, making it a design element. A product suitable to light steps and perimeter walls. Used in series, it creates pleasant graphic effects of light.

MASK



wall recessed

IP65
IK 07

6 mm transparent
extra-clear glass

50 x 205 mm

0,20 m cable length



WHITE LED

3000K CRI>80
12V DC ⚡

2700K / 4000K
available on request



2,8W | 10 lm (*)
asymmetrical



60° x 7°
6000 cd/klm

(*) Real Data

details

Die-cast body and flange made of aluminium alloy with very low copper content. External power supply with 12/24V DC constant-current transformer, to be wired in parallel. Nylon outer casing to be ordered separately. The product is subjected to galvanic anodizing treatment divided into distinct phases: mechanical satin finishing, surface degreasing, anodic oxidation and finally fixing. Subsequently the product is painted by performing a double pass in-line process, which allows you to generate a single thick protective layer which then generates barrier against atmospheric agents and UV rays. This allows to achieve corrosion resistance performance in salt spray. Pre-treatment with atmospheric pressure plasma is carried out on the surface before gluing of the diffuser on Platek products.

standard finish




.06 grey

on request finishes



.01 black



.02 white



.07 corten



.08 anthracite



.09 bronze