

# BALI on pole



# on pole

BALI on pole

ARCHITECTURAL OUTDOOR LIGHTING

Poles with a cylindrical base: Bali is a family of fittings for functional lighting, with a classical design. The wall lights are available in street optic version and rotosymmetric version. Bali is perfect for arcades, gardens, private streets, but also for parkings, cycle tracks and squares. They can normally be installed two luminaires each pole up to 4 meters in height.



BALI on pole

ARCHITECTURAL OUTDOOR LIGHTING

on pole





on pole


IP65  
IK 10

12 mm extra clear glass  
transparent

4 m cable length


ø 200 x h. 290 mm

pole to be ordered separately



ø 200 x h. 290 mm

pole to be  
ordered separately



### WHITE COB LED

→ symmetric

3000K CRI>80  
220-240V 50/60Hz ⊕



26W 3080 lm  
medium

2700K / 4000K  
available on request



38°  
1730 cd/klm

### WHITE 4 LED

→ street optic

3000K CRI>80  
220-240V 0/50/60Hz ⊕



34W 3250 lm  
street optic

2700K / 4000K  
available on request




310 cd/klm

## details

Turned steel body. Die-cast closing flange made of aluminum alloy. A4 Stainless steel screws. The product is subjected to galvanic anodizing treatment divided into distinct phases: mechanical satin finishing, surface degreasing, anodic oxidation and finally fixing. Subsequently the product is painted by performing a double pass in-line process, which allows you to generate a single thick protective layer which then generates barrier against atmospheric agents and UV rays. This allows to achieve corrosion resistance performance in salt spray. Pre-treatment with atmospheric pressure plasma is carried out on the surface before gluing of the diffuser on Platek products.

## finishes

### standard




.06 gray

### finishes on request



.01 black



.02 white



.07 corten



.08 anthracite



.09 bronze

(\*) Real data